








高精度热敏电阻温度传感器

| 参考外形 | 参考尺寸 mm | | | R ₂₅ | 工作温度 °C | 准确度 |
|---|---------|-----|--------|-----------------|---------|-----|
| 元件 | A | B | | | | |
|  | 1.3 | 2.2 | | | | |
| | 0.8 | 1.4 | | | | |
| | 0.5 | 1.1 | | | | |
| 金属外壳 STT-R-10K 系列 | φ | L | | | | |
|  | 2.0 | ≥5 | | | | |
| | 3.0 | ≥10 | | | | |
| | 4.0 | ≥20 | | | | |
| | 5.0 | ≥15 | | | | |
| | 6.0 | ≥30 | | | | |
| 螺纹安装 STT-S-10K 系列 | M | L | | | | |
|  | 3×0.5 | 10 | | | | |
| | 5×0.8 | 10 | | | | |
| | 8×1.25 | 10 | | | | |
| | 10×1.5 | 14 | | | | |
| 带保护管安装 STT-T-10K 系列 | φ | L | M | | | |
|  | 1~1.5 | ≥15 | 3×0.5 | | | |
| | 1~3 | ≥15 | 5×0.8 | | | |
| | 1~4 | ≥15 | 8×1.25 | | | |
| | 1~6 | ≥15 | 12×1.5 | | | |
| | 1~8 | ≥15 | 16×1.5 | | | |
| 带航插连接 STT-C-10K 系列 | φ | L | M | | | |
|  | 1~1.5 | ≥15 | 3×0.5 | | | |
| | 1~3 | ≥15 | 5×0.8 | | | |
| | 1~4 | ≥15 | 8×1.25 | | | |
| | 1~6 | ≥15 | 12×1.5 | | | |
| | 1~8 | ≥15 | 16×1.5 | | | |
| 表面测温 STT-F-10K 系列 | W | L | H | | | |
|  | 10 | 12 | 3.5 | | | |
| | 7 | 7 | 2.0 | | | |
| 壁挂式温度传感器 STT-W | W | L | H | | | |
|  | 55 | 70 | 24 | | | |

5k Ω
10k Ω

0°C~60°C
0°C~100°C
10°C~30°C
20°C~24°C

1mK
2mK
10mK

备注：可定制各种外形尺寸，各种过程接口，例如 VCR, KF, CF 等。

北京赛亿凌科技有限公司

电话 010 62230011

传真 010 62230033